

Achieving stable water distribution and flow rates in simplified hydroponic and aquaponic systems with header tanks

Michael Reuter
APM, Issum, Germany

What is the problem/challenge being solved?

Most hydroponic systems (e.g. Deep-Water Culture (DWC), Nutrient Film Technique (NFT), media beds) rely on a constant but low flow rate of nutrient solution through the plant roots. This ensures a stable supply of water, nutrients, and oxygen, which is essential for healthy plant growth.

In simplified hydroponic and aquaponic systems, water distribution is often driven by elevated header tanks that are periodically refilled, either by pumps or manually. These systems operate under very low hydraulic pressure, which continuously decreases as the header tank empties. In practice, this leads to several recurring problems:

- Changes in flow rates during the emptying cycle of the header tank;
- Low flow rates which are difficult to adjust reliably, especially in parallel systems; and
- Conventional valves clog easily when used with nutrient-rich or aquaponic water.

As a result, plants may receive uneven water and nutrient supply, and system reliability is reduced.

What is the solution developed?

Two simple and complementary design elements were developed to address these challenges:

1. A **flow rate limiter** with constant hydraulic head, installed between the header tank and the water distribution system
2. **Orifice-based flow control** for both sub-distribution and individual cultivation systems.

Together, these measures ensure:

- A constant flow rate, independent of the fill level of the header tank;
- A uniform and adjustable water supply to multiple hydroponic or aquaponic units; and
- High robustness and low risk of clogging, even in aquaponic systems

Solution 1: Constant flow from the header tank

A small container, also called a **flow rate limiter**, is installed between the header tank and the sub-distribution system (Figure 1). The inflow into this container is controlled by a low-pressure float valve.




Figure 1: Example of a simplified hydroponic system build from 220-litre blue open-head barrels. It consists of header tanks, 6 media beds with individual inflows as cultivation systems, and a sump tank. The flow rate limiter is located between the two storage tanks.

The float valve maintains a constant water level inside the flow rate limiter, regardless of the changing water level in the header tank. This creates a constant hydraulic head at the outlet(s) of the limiter (Figure 2).




Figure 2: The water level (h) in the flow rate limiter is regulated by the low-pressure float valve. Regardless of the fill level of the header tanks, this water level always remains the same. The flow rate is determined by the water level and the diameter (d) of the orifice in the metal disc at the outlet.

At the bottom of the flow rate limiter, one or more orifices are installed, each supplying a defined sub-distribution. The combination of a constant water level (h) and a fixed orifice diameter (d) results in a stable and predictable volume flow.

Fine adjustment of the flow rate can later be achieved by slightly changing the float position. A higher water level increases flow; a lower water level reduces it.

To allow flexibility, it is advisable to design the outlets so that orifice discs can be exchanged. If this is not possible, drilled end caps can be used. In this case, reducing material thickness at the orifice (e.g. with a countersink) improves accuracy.

For stable operation, the total flow through the flow rate limiter should closely match the sum of the flow rates required by the connected sub-distributions.

There is a small orifice at the bottom of the flow rate limiter for each sub-distribution that is to be supplied with water. The size of the orifice and the constant water level result in a constant volume flow into the sub-distribution.

The expected flow rate can be estimated using the standard orifice equation (see formula below), but in practice it is recommended to verify the actual flow using a measuring cylinder during system setup.

$$Q = C_d \times A \times \sqrt{2 \times g \times h}$$

with

Q	m ³ /s	volumetric flow rate
C _d	-	discharge coefficient (approx. 0.62 for a sharp-edged orifice)
A	m ²	cross sectional area of orifice
g	m/s ²	gravitational acceleration
h	m	vertical head over the orifice center

The actual volume flow through the outlets can be fine-tuned later by adjusting the position of the floater on the valve. A higher water level in the flow limiter results in a higher volume flow. A lower water level reduces it.

Tables 1 and 2 provide example flow rates and a system sizing example.

Table 1: Flow rates for different water levels (h) in the flow rate limiter, depending on the diameter (d) of the orifice in the perforated metal disc.

Flow Rates [l/h]								
	Orifice Diameter [mm]							
Water Level [mm]	1	1.5	2	2.5	3	3.5	4	5
80	2.2	4.9	8.8	13.7	19.8	26.9	35.1	54.9
100	2.6	5.5	9.8	15.3	22.1	30.1	39.3	61.4
120	2.7	6.1	10.8	16.8	24.2	33	43	67.2
140	2.9	6.5	11.6	18.2	26.1	35.6	46.5	72.6
160	3.1	7	12.4	19.4	28	38	49.7	77.6

At the same time, it is useful to design the flow rate limiter so that the orifice discs at the outlets can be replaced. If this design is too expensive, the outlet can also be closed with an end cap and a hole simply drilled into it. If possible, the material thickness at the outlet should be reduced with a countersink drill bit in this case. Otherwise, the volume flow will be reduced compared to the initial calculation.

For the overall system, it is important that the volume flow through the flow rate limiter corresponds as closely as possible to the sum of the planned volume flows in the respective sub-distribution.

Table 2: Example of a system with 3 media beds supplied with water via a 1" supply line. The diameter of the holes in the orifice discs (d_1) is determined by the water level in the outlet (h_1). The water level in the flow rate limiter (h_2) is adjusted using the float of the float valve. This determines the correct diameter for the outlet (d_2) in order to provide the amount of water required by the sum of the media beds.

Component	Flow Rate [l/h]	h_1 [mm]	d_1 [mm]
Media Bed 1	10	21	3
Media Bed 2	10	21	3
Media Bed 3	10	21	3
Sum	30		
		h_2 [mm]	d_2 [mm]
Flow Rate Limiter	30	100	3.5

Solution 2: Uniform sub-distribution to cultivation systems

From the flow rate limiter, water is routed without pressure through an open gutter or slightly inclined supply line to the individual cultivation systems (Figure 3). A small slope ensures reliable flow and prevents unwanted pooling.




Figure 3: The supply line to the cultivation systems must be designed with a slight slope to ensure sufficient flow. This allows the individual outlets to fill with water and the excess water to flow quickly to the next outlet.

Each outlet to a cultivation system is designed as a tee in which water can temporarily accumulate. The lower end of the tee is closed with an orifice disc, creating a constant hydraulic head above the orifice. This ensures a stable flow rate into each cultivation unit, independent of upstream fluctuations.

As with the flow rate limiter, replaceable orifice discs are recommended. Alternatively, drilled end caps can be used.

A maintenance opening above each outlet allows quick inspection and cleaning, which is particularly useful in aquaponic systems where fine solids may occur (Figure 4).

Table 3 shows typical flow rates for 1" tees with different orifice diameters.




Figure 4: If the outlets are designed with screw caps, the diameter of the orifice can be easily changed by replacing the metal disc. This allows the flow rate to be adjusted at any time. The maintenance hole allows any potential dirt in the outlet to be quickly and easily removed.

Table 3: Flow rates for typical 1" tees that create a hydraulic head of approximately 21 mm (h), depending on the diameter of the hole in the orifice disc.

	Flow Rates [l/h]							
	Orifice Diameter [mm]							
	1	1.5	2	2.5	3	3.5	4	5
1"-Tee (h=21 mm)	1.1	2.5	4.5	7	10.1	13.8	18	28.1

Practical notes

The system works reliably for flow rates between approximately 1 and 40 L/h per cultivation unit.

Multiple orifices or combinations of hole diameters can be used to achieve intermediate flow rates.

For custom-built components, the actual discharge coefficient can be determined experimentally by measuring flow rates at known water levels. This allows more accurate planning of future systems using the same parts.

Why this matters in practice

This approach provides a low-cost, low-tech, and highly reliable solution for water distribution in simplified hydroponics and aquaponics with low water pressure (small headroom). It avoids complex valves, compensates automatically for changing water levels, and is well suited for systems built from locally available materials.